

Setback/Coverage Calculations

(Lots 65' or less in width)

For Principal Dwelling/Cottage Dwelling/Single Family/Duplex (R-2) District

Address: _____ Lot Width: _____

Submitted by: _____ Lot Area: _____

Principal Dwelling _____ Cottage Dwelling _____ Single Family Residence _____ Duplex _____

	Existing <u>Area</u>	+	Proposed <u>Area</u>	=	Total <u>Area</u>	Permitted <u>Area</u>
Minimum Living Area (sq.ft.)						
Principal Dwelling	1,000					
Cottage Dwelling	500					
Single Family	1,000					
Duplex	1,000					

Impervious Lot Coverage

{include all areas from above at grade level plus all driveways, sidewalks, patios, pools, artificial turf, etc}

Principal Dwelling - 65%						
Cottage Dwelling - 65%						
Single Family - 65%						
Duplex - 60%						

Maximum Building Coverage

Principal/Cottage dwelling 35%						
Single Family - 40%						
Duplex - 35%						

Floor Area Ratio (FAR)*

For 2-Story Buildings only

{include 1st & 2nd floors, garage, carports, porches, accessory bldgs, & EXCLUDE pool screen enclosure}

Principal Dwelling - 30%						
Cottage Dwelling - 20%						
Single Family - 55%						
Duplex - 50%						

(Note 1)

Excludable Area of Porches (sq.ft.) from FAR

Principal Dwelling	400					
Cottage Dwelling	300					
Single Family	700					
Duplex	600					

(Note 2)

Building Height Maximum Permitted: 30' Proposed Height: _____ (above existing grade)
 Maximum Building Stories - 2

Two parking spaces per unit required behind front setback line, except only 1 space for a cottage dwelling.

Stormwater retention required per the Land Development Code.

*Applies to two-story building only; FAR is the total gross building area divided by the total lot area. Common driveways are permitted between two adjoining lots.

Setbacks R-2
(Lots 65' or less in width)

	EXISTING	PROPOSED
<u>FRONT SETBACKS</u>		
To first floor wall – 25'	_____	_____
To second floor wall – 30'	_____	_____
<u>SIDE SETBACKS</u> (Principal/cottage, dwelling or duplex)		
To first floor wall (note 3) – 7'	_____	_____
Driveway side first floor wall (note 4) – 11'	_____	_____
To second floor wall – 10'	_____	_____
<u>Rear setbacks</u>		
One Story Building - 10'	_____	_____
Two Story Building - 25' (note 6)	_____	_____
<u>Corner Lot Setbacks**</u>		
Lot width 65' or less – 14'	_____	_____

Open Front Porch & Entryway allowance: An additional projection of up to 7' into the required front setback is permitted on any R-2 property.
All setbacks given are minimum allowed

*Required if garage is located in rear of lot, otherwise garage must be set back 35' from front lot line and at least 4' behind front of building, and one story garage is permitted a setback of 7'.

**Corner lot setbacks are measured on the side yard adjacent to the street, where the street side having the least frontage is determined to be the front.

Notes:

1. If a single-family residence, only, is built on the lot, the maximum floor area ratio is 55%. The maximum total floor area ratio on a property developed with a principal dwelling and a cottage dwelling shall be 50% with the principal dwelling having a larger gross floor area than the cottage dwelling.
2. Only open porches in the front and screened or open porches in the rear and side of the principal and cottage dwelling may be excluded from the floor area ratio up to a total area of 700 square feet.
3. The 7-foot side setback shall only be permitted on one side of the lot, and a 5-foot side setback to an attached or detached garage or carport shall be permitted on either side of an interior lot subject to limiting the building wall height to 8 feet and limiting the building wall length to 22 feet.
4. The 11-foot side setback shall be provided on one side of an interior lot to the first and second floor walls to allow driveway access. Where two abutting properties utilize one common driveway, the side setback may be 10 feet.
5. For duplexes, side building walls over 20 feet in length and over 17 feet in height above the existing grade must be set back an additional 5 feet from the lot line at the second floor wall and continue at the additional 5 foot setback for at least 10 feet along the side of the building before returning to the 10 foot side setback. Alternate methods to accomplish this relief from having long two story boxlike buildings along the side lot line may be approved by staff.
6. For lots that have rear lot lines adjoining non-residential zoning, the second floor setback may be 10 feet.

SEE ORDINANCE FOR ADDITIONAL PROVISIONS; THIS WORKSHEET DOES NOT COVER ALL REQUIREMENTS

Attachments to R-2 Setback/Coverage Worksheets

Other provisions and allowances for R-2 District Developments: (Excerpts from Ordinance)

(3) Additional Development standards (lots 65 feet or less in width):

1. Parking shall be provided behind the front dwelling with only one driveway entering the property.
2. The driveway and parking surface setback is permitted to be one foot from the rear or side lot line subject to providing a design which will not cause additional drainage onto a neighboring property.
3. The required off-street parking shall be two spaces for the principal building, one space for the cottage dwelling, and two spaces per unit for a duplex.
4. Circular driveways and parking in front shall be prohibited.
5. No front entry garages are permitted, except when provided in the rear half of the lot or on a corner lot.
6. Open front porches or covered entryways must be provided or a similar alternate front entryway must be provided.
7. The principal dwelling may be placed in either the front or the rear of the lot.
8. For corner lots the street side setback shall be 14 feet and the interior side setback shall be 7 feet to the first floor wall only. Other site development requirements remain the same as established for lots 65 feet or less in width.
9. The area between the building and the street shall be landscaped with grass, plantings or both, and any unusual designs shall be subject to the approval of the Parks Director.
10. Screen pool enclosures may also be permitted an additional eight (8%) percent of the lot area in addition to the permitted building area.
11. Minor deviations of the floor area ratio for a principal dwelling and a cottage dwelling may be considered up to plus or minus one percent (1%).
12. When utilizing one common driveway between two properties, the required side setback of eleven (11) feet may be reduced to seven (7) feet to the first floor wall and ten (10) feet to the second floor wall.

(4) Additional Development standards for development of a single-family residence only:

1. Front entry garages are permitted if set back at least 35 feet from the front property line, and placed behind the front building line of the dwelling by at least four (4) feet.
2. The eleven (11) foot side setback shall be required if the garage is at the rear of the lot. If no driveway around the home is provided, then a seven (7) foot side setback shall be observed to the first floor wall, and the second floor setback shall be ten (10) feet to the second floor wall from the side lot line.
3. All other provisions of the development standards for lots 65 feet in width or less shall apply where applicable.

(5) Development Standards for all properties in the R-2 District:

1. A minimum distance of 22 feet shall be provided in front of garages and carports for parking turn around space, except on corner lots a minimum distance of twenty (20) feet may be permitted in front of a garage.
2. One common drive may serve two abutting properties without meeting the driveway setback requirement.
3. The architecture of the front of the building shall not included two story high features such as entry areas, porches or columns unless set back at least thirty (30) feet from the front lot line.
4. Open front porches or covered entryways may encroach up to seven (7) feet into the required front setback. A porch depth of eight (8) feet or more is requested for functionality.

5. Minimum living area. The minimum living area of any single-family residence shall be on thousand (1,000) square feet. The minimum living area of duplex or cluster residential units shall average seven hundred fifty (750) square feet but no individual unit shall be less than four hundred (400) square feet.
6. Properties or lots exceeding 10,000 square feet are permitted building heights of thirty-five (35) feet if the side setback is increased to twenty (20) feet measured to the roof component of the building over thirty (30) feet in height.

(6) Additional Development standards for R-2 lots which abut single family zoned properties:

1. The rear yard setback shall be 25 feet to the first floor wall and 35 feet to the second floor wall, except where the abutting single family zoned property is not used for residential purposes, such as churches, parks, community centers, etc.
2. The maximum floor area ratio shall be 45%, except a single-family dwelling may utilize a floor area ratio of 55%.
3. All building plans for duplexes shall require appearance review approval by the Town Designer or Planning Department designee in accordance with criteria listed under (e)(2) of this Section. Appeals of the appearance review determination of the Town Designer may be made by the applicant and shall be heard by the Planning and Zoning Commission within 40 days of receipt of the appeal request. The applicant or city staff may appeal the decision of the Planning and Zoning Commission to the City Commission within 15 days from the date of that decision. The matter shall be heard by the City Commission within 30 days for final determination.

- (b) Stormwater control. Duplex and cluster housing shall provide onsite stormwater retention as provided by the land development code.

SECTION 2. Chapter 58 "Land Development Code", Article III "Zoning" of the Code of Ordinances is hereby amended and modified by adding to SECTION 58-82 "General Provisions" subsections (kk) and (ll) to read as follows:

- (kk) First or second floor walls of buildings in residential zoning districts shall not extend above the top plate of the first floor for one story buildings or above the second floor top plate of two story buildings so as to create additional wall height or the appearance of an additional story unless such area is part of the allowable floor area and meets the required setbacks. This limitation does not prevent the provision of a parapet wall for flat roof buildings.
- (ll) The required two-story setback shall apply to walls, which extend twelve (12) feet in height or more above the existing pre-construction grad for buildings in residential zoning districts.

February 4, 2003